

Model Number: Accessories: Job:	Approvals:  Type:
---------------------------------------	-------------------------

**FEATURES**

- Reliable illumination – requiring no additional electricity to operate
- Ultra-compact, low-profile design
- Designed for both high- or low-level installations
- Non-toxic, non-radioactive materials
- Low cost - easy installation
- Requires virtually no maintenance with periodic inspections for over 25 years
- Universal Mounting - Ceiling, back or end mount
- Constant, uniform illumination – visible at 50 feet in total blackout or heavy smoke conditions
- Available in framed and unframed faces with colors: red, green, black or white

**CONFORMANCE TO CODES AND STANDARDS**

Listed to UL 924, IEC ES #6040 meeting all current building codes: 1997 Uniform Building Code™, the 2000 International Building Code®, the BOCA® National Building Code/1999 and the 1999 Standard Building Code®. Meets NFPA Life Safety Code 101® and 101B®, NFPA 5000 Building Construction & Safety Code™, 1998 California Building Code, 1998 California Fire Code, 2003 International Building Code® and OSHA.



SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

**ORDERING INFORMATION Example: PL-1-F-1-B**

Exit Black	Exit Red	Exit Green	Exit White	Sortie Red	
PL-1-F-1-B	PL-1-F-1-R	PL-1-F-1-G	PL-1-F-1-W	PL-1-F-1-R-S	Single Face Sign (Wall Mount)
PL-1-F-2-B	PL-1-F-2-R	PL-1-F-2-G	PL-1-F-2-W	PL-1-F-2-R-S	Single Face Sign w/ Mounting Bracket
PL-2-F-2-B	PL-2-F-2-R	PL-2-F-2-G	PL-2-F-2-W	PL-2-F-2-R-S	Double Face Sign w/ Mounting Bracket
PL-MB-B	PL-MB-R	PL-MB-G	PL-MB-W	PL-MB-R	Mounting Bracket
PL-CMC					Clear Mounting Clip (4 pc/bag & 10 bag/case)

## TECHNICAL INFORMATION

Sizes:	8.25" x 15.25" x .25" (Sortie 8" x 22.1875" x .25")
Letter size:	.875" stroke with 7" height
Background:	Black, Red, Green or White
Illumination:	High Visibility Green
Visibility:	50 feet
Directional:	Pop-out chevron arrows for easy direction selection
Construction:	.035 steel and a plastic photoluminescent panel
Durability:	Explosion-proof for areas requiring explosion-proof exit signage
Tests Passed:	UL 924 Emergency Lighting and Power Equipment Listed through UL; ICC ES #6040, CA State Fire Marshall Listing #6200-1617; 100; City of Los Angeles Research Report: RR 25531 (CSI #16530) Ontario Building Material Evaluation Commission Authorization Report BMEC #03-12-291
Life Expectancy:	25+ years
Power Requirements:	No additional electrical or mechanical source required
Installation:	Surface, flag or ceiling mounted (hardware included). Before installation it must be determined that there is a minimum of 54 lux of ambient fluorescent, metal halide or mercury vapor light on the face(s) of the sign at all times during occupancy.
Applications:	Both high-level and low-level



Shown: Exit with clear mounting clips (PL-CMC)

*Check out these other important products in our Exi-Glow Photoluminescent Life Safety Egress System: Pathway Marking Strips, Safety Signage, Dots and Arrows and Safety Tapes.*

Model Number: Accessories: Job:	Approvals:  Type:
---------------------------------------	-------------------------

**FEATURES**

- Reliable illumination – requiring no additional electricity to operate
- Ultra-compact, low-profile design
- Designed for both high- or low-level installations
- Non-toxic, non-radioactive materials
- Low cost - easy installation
- Requires virtually no maintenance with periodic inspections for over 25 years
- Universal Mounting - Ceiling, back or end mount
- Constant, uniform illumination – visible at 50 feet in total blackout or heavy smoke conditions
- Available in framed and unframed faces with colors: red, green, black or white

**CONFORMANCE TO CODES AND STANDARDS**

Listed to UL 924, IEC ES #6040 meeting all current building codes: 1997 Uniform Building Code™, the 2000 International Building Code®, the BOCA® National Building Code/1999 and the 1999 Standard Building Code®. Meets NFPA Life Safety Code 101® and 101B®, NFPA 5000 Building Construction & Safety Code™, 1998 California Building Code, 1998 California Fire Code, 2003 International Building Code® and OSHA.



SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

**ORDERING INFORMATION Example: PL-U-1-R**

Exit Red	Exit Green	Sortie Red	
PL-1-U-1-R	PL-1-U-1-G	PL-1-U-1-R-S	Single Face Sign (Wall Mount)
PL-1-U-1-R-RL	PL-1-U-1-G-RL		Single Face Sign w/ Reflective Letters (Wall Mount)
PL-1-U-1-R-NY			Single Face Sign w/ 8" Printed Letters for NYC (Wall Mount)

## TECHNICAL INFORMATION

Sizes:	7.5" x 13" x .075" (7280 = 10" x 17" x .075")(Sortie 7.5" x 18.125" x .075")
Letter size:	.8125" stroke with 6" height (7280 = 1" stroke with 8" height)
Background:	Photoluminescent
Illumination:	High Visibility Green
Visibility:	50 feet
Directional:	2 included
Construction:	Plastic photoluminescent panel/red or green lettering
Durability:	Explosion-proof for areas requiring explosion-proof exit signage
Tests Passed:	UL 924 Emergency Lighting and Power Equipment Listed through UL; ICC ES #6040, CA State Fire Marshall Listing #6200-1617; 100; City of Los Angeles Research Report: RR 25531 (CSI #16530) Ontario Building Material Evaluation Commission Authorization Report BMEC #03-12-291
Life Expectancy:	25+ years
Power Requirements:	No additional electrical or mechanical source required
Installation:	Surface mounted. Before installation it must be determined that there is a minimum of 54 lux of ambient fluorescent, metal halide or mercury vapor light on the face(s) of the sign at all times during occupancy.
Applications:	Both high-level and low-level

*Check out these other important products in our Exi-Glow Photoluminescent Life Safety Egress System: Pathway Marking Strips, Safety Signage, Dots and Arrows and Safety Tapes.*