KONE II OPAL GLASS LUMINAIRE WITH DOWNLIGHT



TYPE: PROJECT:

ORDER NUMBER:

Model# Wattage Voltage Option

26, **32**, **42 1**–120V **EM**–Emergency battery or **57** CFL **2**–277V

| Dimming: | 70 or 100 | D3, D4, D5, D8 or D9 | Metal Halide | (See Back Page) |

Example:


6232	26	1	EM

KONE OPAL PENDANT


Canopy mounts to standard J-box. Electronic ballast fits inside fixture for easy access. Pendant is 6' standard with push button adjustable aircraft cable. Finish is silver, with white power cord. The opal glass shade is removable without tools and is for general illumination, with an interior clad aluminum downlight relector for task lighting. Fixtures feature twist lock socket for secure, easy relamping. Dimming and emergency options are available. U.L. listed for damp locations.

6232

Fluorescent



6233 Metal Halide 70/100W



DELRAY LIGHTING INCORPORATED

BURBANK,

CALIFORNIA,

91505


www.

DELRAY


LIGHTING.

COM

1-42W PLT



CP DISTRIBUTION



COEFFICIENTS OF UTILIZATION

% CEI	LING 80 LL 70	(20% 50	FLOOR) 30
0	73	73	73
1	65	61	58
2	59	54	49
3	54	48	42
4	50	43	37
5	46	39	33
6	43	35	30
7	40	32	27
8	37	29	24
9	35	27	22
10	33	25	20

NOTES

6232.42

1-42W triple tube G24q-3 electronic twist lock socket Total lumens: 3200 Spacing criteria: .78

METAL HALIDE


Use only medium base, coated and protected, ceramic metal halide ED17 lamps.

DIMMING

- Ballast mounted inside fixture.
- Voltage *must* be specified.
- Controls lumen output down
- Compatible dimmers required for all ballasts.
- D3 Advance Mark X for 26, 32 or 42W lamp.
- **D4** Lutron Tu-Wire for 26 or 32W lamp. 120V *only*. **D5** Advance Mark VII for 26,
- 32 or 42W lamp.
- **D8** Lutron Hi-Lume 1% for 26 or 32W lamp. Controls lumen output down to ±1%.
- **D9** Lutron EcoSystem for 18, 26, 32 or 42W lamp. Controls lumen output down to ±5%.

EMERGENCY

- Voltage must be specified.
- EM emergency power provides 650 lumens for one lamp for 90 minutes. Ht.=14.375"
- EM13 emergency power provides 1300 lumens for one lamp for 90 minutes. Ht.=19"



AL-Acrylic Lens. For security and food service installations. Use with CFL lamps only.