

PR Series

Protek Round



General Characteristics:

Lamp Type: Compact Fluorescent or

LED

Ballast Type: Electronic
Standard Voltage: 120-277
Options: Photocell
Mounting: Wall or Ceiling

Additional Info.: UL Listed and Title 24


Compliant


Catalog No. Type: Job Name:

Features & Specifications:

The Protek Series is a fully gasketed enclosed fixture designed to prevent dust, moisture, and insects from entering. This drum shaped fixture is suitable for indoor and outdoor applications. Ideal for stairways, hallways and garages or any applications that call for weather or vandal proof fixtures.

- High performance electronic ballast
- Polycarbonate base and diffuser
- Available in black or white base with white or frosted prismatic diffuser
- White powder coated steel gear tray
- Available in a variety of lamp configurations
- Photocell available
- Molded of durable UV resistant plastic
- Vandal resistant
- UL listed for wet location





Catalog Ordering: Example: PR13B-20-PC

PR







Г			

FAMILY TYPE	WATTAGE	BODY	LENS	OPTION
PR	13 (1- 13 WT CFL)	B (Black)	-10 (Clear)	PC (Photocell)
	213 (2- 13 WT CFL)	W (White)	-20 (White)	
	GU13 (1- 13 WT GU24)			
	GU213 (2- 13 WT GU24)			
	18 (1- 18 WT CFL)			
	218 (2- 18 WT CFL)			
	GU18 (1-18 WT GU24)			
	GU218 (2- 18 WT GU24)			
	L1800 (1800lm 18WT LED)			

Specifications and Dimensions Subject to change without notice

FSC 12120 Altamar Place, Santa Fe Springs, CA 90670 Ph 562-906-2644 Fax 562-906-2649

