LIGHTOLIER®

Skyway

Recessed Fluorescent





Lightolier is a Philips group brand

PHILIPS

Skyway Appearance


Skyway's aesthetically pleasing triple lens design features a clear conical prismatic center lens, enhanced by softly curved frost white acrylic lenses on each side, mounted in a regressed extruded aluminum frame with spring loaded latches. These 85% light transmission lenses, coupled with an internal reflector system coated with our 95% reflective white paint, produce our new, energy efficient Skyway.


Skyway Performance

42 Skyway 2' x 4' Fixtures	60' x 56' x 9' Room			Reflectance 80/50/20				
Catalog Number	Ballast Factor	Efficiency	Total Light Loss Factor	Average Footcandles	Max/Min Uniformity	Input Watts	Watts/ Sq. Ft.	Energy Savings
SKS2GPK232UNVC5 Instant start ballast, 2-T8 3100 lumen lamps	0.77	75.3%	0.67	42.5	1.6 : 1	48	0.60	40%
SKS2GPK232UNVC2 Instant start ballast, 2-T8 3100 lumen lamps	0.87	75.3%	0.76	48.0	1.6 : 1	54	0.68	33%
SKS2GPK228UNVPG Prgm. rapid start ballast, 2-T5 2750 lumen lamps	0.95	73.0%	0.83	46.5	1.6 : 1	57	0.71	29%

60' 56' 56'

* This layout of Skyways will consume 29% to 40% less energy than the current LEED requirement of 1.0 watts per square foot depending on the ballast used. Footcandle readings are 2 1/2 ft off the floor 2 1/2 ft on center.





42 Skyway 2' x 2' Fixtures	60' x 56' x 9' Room			Reflectance 80/50/20				
©atalog Number	Ballast Factor	Efficiency	Total Light Loss Factor	Average Footcandles	Max/Min Uniformity	Input Watts	Watts/ Sq. Ft.	Energy Savings
SKS2GPK2FTUNVIB Instant start ballast, 25 watt TT5 2300 lumen lamp	0.92	89.9%	0.80	45.0	1.5 : 1	59	0.74	26%
SKS2GPK2FTUNVIB Instant start ballast, 40 watt TT5 3300 lumen lamp	0.88	76.5%	0.77	52.7	1.5 : 1	69	0.86	14%
SKS2GPK224UNVPG Prgm. rapid start ballast, 2-T5 2000 lumen lamps	1.1	73.0%	0.83	46.5	1.6 : 1	57	0.71	29%

* This layout of Skyways will consume 14% to 29% less energy than the current LEED requirement of 1.0 watts per square foot depending on the ballast used. Footcandle readings are 2 1/2 ft off the floor 2 1/2 ft on center.

Skyway Offering

Skyway Fixtures

Catalog Number	Fixture Size	Number of Lamps	Lamp Type	Ballast Type	Ballast Factor
SKS2GPK2FTUNVIB	2' X 2'	2	40W TT5	Instant Start	0.88
SKS2GPK224UNVPG	2' X 2'	2	24W T5HO	Program Rapid Start	1.1
SKS2GPK324UNVPG	2' X 2'	3	24W T5HO	Program Rapid Start	1.1
SKS2GPK217UNVHI	2' X 2'	2	17W T8	Instant Start	0.87
SKS2GPK317UNVH3	2' X 2'	3	17W T8	Instant Start	0.87
SKS2GPK417UNVH4	2' X 2'	4	17W T8	Instant Start	0.87
SKS2GPK26UUNVHI	2' X 2'	2	32W 6"U T8	Instant Start	0.87
SKS2GPK228UNVPG	2' X 4'	2	28W T5	Program Rapid Start	0.95
SKS2GPK328UNVPG	2' X 4'	3	28W T5	Program Rapid Start	0.95
SKS2GPK254UNVPG	2' X 4'	2	54W T5HO	Program Rapid Start	1.0
SKS2GPK232UNVC5	2' X 4'	2	32W T8	Optanium Instant Start	0.77
SKS2GPK232UNVC2	2' X 4'	2	32W T8	Optanium Instant Start	0.87
SKS2GPK332UNVH3	2' X 4'	3	32W T8	Instant Start	0.87

For Air Handling Skyway 2' X 2' or 2' X 4' change SKS to SKA when ordering. Modles for New York City code and Chicago Plenum are avalible.

Lightolier is a Philips group brand

631 Airport Road Fall River, MA 02720 Phone (508) 679-8131 Fax (508) 674-4710 www.lightolier.com

3015 Rue Louis Amos Lachine (Quebec) H8T 1C4 Phone (514) 636-0670 www.canlyte.com

© 2008 Philips Group. All rights reserved. Certain products illustrated in this catalog may be protected by applicable patents and patents pending. Lightolier will aggressively defend all of its intellectual property. We reserve the right to change details of design, materials and finishes.

A.I.A. Division 16 Brochure LOL7120 Folio MA12-05

Some luminaires use fluorescent or high intensity discharge (HID) lamps that contain small amounts of mercury. Such lamps are labeled "Contains Mercury" and/or with the symbol "Hg." Lamps that contain mercury must be disposed of in accordance with local requirements. Information regarding lamp recycling and disposal can be found at www.lamprecycle.org.