

Aluline 111



Product Description

- Low-voltage halogen reflector lamp with high-purity aluminium reflector of 111 mm

Product Features

- Metal cap to shield filament to reduce glare and improve beam shape
- G53 socket and screw or tab terminals allowing for direct wire connection with imating eyelet or receptacle
- UV-block quartz glass

Product Benefits


- Glare free, well defined accent lighting with minimum amount of direct glare from the lamp

Application

- Excellent light source for general lighting and especially creative accent lighting in shops, restaurants, hotels, galleries, exhibitions and museums

Luminaires

- For use in open luminaires



C	C1	D
max.	max.	max.
61	50	111

Aluline 111 G53 12V

Lamp Wattage		Luminous Intensity	Life to 50% failures	Packing type/Packing configuration	Packs per outer box	National Order Code	Ordering number 8711500...	Nett Trade Price per Piece (£)
(W)	(°)	(cd [max.])	(h)					
50	8	23000	3000	1CT / 6X1F	6	14634	426529 33	26.64
50	24	4000	3000	1CT / 6X1F	6	14635	426550 33	26.64
75	8	30000	3000	1CT / 6X1F	6	14641	426987 33	26.64
75	24	5300	3000	1CT / 6X1F	6	14642	427007 33	26.64
75	45	1900	3000	1CT / 6X1F	6	14643	427021 33	26.64
100	8	48000	3000	1CT / 6X1F	6	14644	427045 33	26.64
100	24	8500	3000	1CT / 6X1F	6	14645	427069 33	26.64
100	45	2800	3000	1CT / 6X1F	6	14646	427083 33	26.64

Aluline 37/56



Product Description

- Low-voltage halogen burner in a lightweight, high-gloss anodised aluminium reflector giving a white halogen light

Product Features

- Integrated protective front glass
- Choice of clear or frosted glass


- High-intensity beam with an extremely clearly defined beam spread (clear glass versions only)
- Excellent colour rendering

Product Benefits


- Excellent accent lighting effects due to reduced spill light (clear versions only)

Application

- Excellent light source for accent and general lighting in shops, home, restaurants, galleries, exhibitions and museums



Dim. no.	C	D
	max.	max.
1	41	38



Dim. no.	C	D
	max.	max.
2	60	58

Aluline

Bulb	Lamp Wattage	Cap-Base	Vol-tage	Bulb Finish		Luminous Intensity	Life to 50% failures	Dim. no.	Packing type/ Packing configuration	Packs per outer box	National Order Code	Ordering number 8711500...	Nett Trade Price per Piece (£)
	(W)		(V)	(°)		(cd [max.])	(h)						
R37	15	BA15d	6	Clear	6	5200	2000	1	1CT / 10X5F	50	6424	401915 60	33.77
R56	15	SBC	6	Clear	4	11000	2000	2	1CT / 10X5F	50	6425	401922 60	33.77
R37	20	BA15d	12	Clear	6	6400	2000	1	1CT / 10X5F	50	6433	401946 60	33.77
R37	20	BA15d	12	Clear	18	1500	2000	1	1CT / 10X5F	50	6434	401953 60	33.77
R37	20	BA15d	12	Frosted	32	350	2000	1	1CT / 10X5F	50	6435FR	409355 60	33.77
R56	35	SBC	6	Clear	6	18000	2000	2	1CT / 10X5F	50	6429	401977 60	33.77
R56	35	SBC	6	Clear	14	4400	2000	2	1CT / 10X5F	50	6430	401984 60	33.77
R56	50	SBC	12	Clear	10	12000	2000	2	1CT / 10X5F	50	6438	402004 60	33.77
R56	50	SBC	12	Frosted	25	2000	2000	2	1CT / 10X5F	50	6439FR	409348 60	33.77