

120/277v/ Outdoor / Bridgelux Chip / includes mounting arm / UL Listed



LED AREA LIGHT

Technical Specifications :

- Catalog number: LR-35CW-P (Cool White, 5000K)
- Catalog number: LR-35NW-P (Natural White, 4100K)
- Catalog number: LR-50CW-P (Cool White, 5000K)
- Catalog number: LR-50NW-P (Natural White, 4100K)
- Lumens: 2800 (35W) / 3800 (50W) CRI: 82
- Housing: Die-cast aluminum with bronze powder coat finish
- Door frame: Die-cast aluminum with four stainless steel retention screws
- Lens: Tempered glass with seamless silicon gasket
- Isolated driver compartment for improved thermal management
- Working Voltage: 120—277 volts (.45 amps maximum at 120 volts)
- LED Bridgelux Chip (COB)
- Power factor: 95% +
- Suitable for wet Locations, stainless steel hardware included
- Maximum Ambient 40 deg C (104 deg F)

Features:

- Wall mounting bracket and arm included (See diagram A)
- Includes NEMA twist-lock photo cell for dusk to dawn operation



DIMENSIONS:

L: 13-3/4" H: 5-1/4" W: 9-1/2"

QUICK SHIP

Catalog Number	Chip	Watts	Voltage	Color Temp	Notes
LR-35CW-P	Bridgelux COB	35 watts	120/277V A/C	CW 5000K	Includes mounting arm & photo ctrl
LR-35NW-P	Bridgelux COB	35 watts	120/277V A/C	NW 4100K	Includes mounting arm & photo ctrl
LR-50CW-P	Bridgelux COB	50 watts	120/277V A/C	CW 5000K	Includes mounting arm & photo ctrl
LR-50NW-P	Bridgelux COB	50 watts	120/277V A/C	NW 4100K	Includes mounting arm & photo ctrl

L1

LED LIGHTING