

SHOP NOW	>
----------	---

Project Name: Type: Quantity:

FIXTURE SPECIFICATIONS

INTENDED USE

The specification grade Alcon Lighting Arc Architectural Fluorescent Linear Indirect Pendant Lighting delivers a reflection of soft and diffused uplight to commercial and hospitality interior lighting applications. Our modern, slim profiles and stylish linear chandelier designs offer excellent indirect lighting, exceptional performance and versatility in offices, banks, retail, educational environments, and more. The Arc Fluorescent linear pendant lighting is available in standard lengths of 4' and 8' and can be joined together in seamless runs of any length.

AVAILABLE LENGTHS

4FT | W 9" x L 48" x H 3" 8FT | W 9" x L 96" x H 3"

Continuous Run | Consult Factory

FEATURES

Construction: Die-Formed and Welded 20-Gauge Cold Rolled Steel. Flat End Steel Plate Standard, Die

Cast Aluminum Spade End Cap Optional

Reflector: Die-Formed High Reflective White Reflector

Distribution: 100% Uplight, Indirect

Lamp: Medium Bi-Pin Twist-Lock Lamp Sockets

Finish: Powder Coated **Technology:** Fluorescent Voltage: 120-277V **THD:** <10%

Life: > 50,000 Hours

Warranty: 5 Years Carefree for Parts & Components (Labor Not Included), 10 Year Option Available


Listing: UL / cUL Listed, Suitable for dry and damp locations, ARRA Compliant




Shown with optional Decorative End Cap (DEC)




Shown without optional Decorative End Cap (DEC)





Shown with 2 Lamps



Shown with 3 Lamps









ORDERING INFORMATION Example: (10119-4-2-18-T-AC48-WH-DEC)

4 4 Foot 8 8 Foot	(Per 4 Foot Section)	T T Day Cailing			
• 01000	2-32 2 Lamps 32 Watts F32-T8 Lamp Not Included 2-54 2 Lamps 54 Watts F54-T5HO Lamp Not Included	T T-Bar Ceiling H Drywall Hard Ceiling	AC48 Standard 48" Adjustable Cable AC96 96" Adjustable Cable	WH White Standard BK Black SL Silver	DEC Decorative End Cap OS Occupancy Sensor EM-120 Emergency Ballast (120V) EM-277
	3-32 3 Lamps 32 Watts F32-T8 Lamp Not Included 3-54 3 Lamps 54 Watts F54-T5HO	mp Not Included 5HO			Emergency Ballast (277V) DM7-120-277V Dimming Ballast Mark 7 (120-277V) 10W
		2-54 2 Lamps 54 Watts F54-T5H0 Lamp Not Included 3-32 3 Lamps 32 Watts F32-T8 Lamp Not Included 3-54 3 Lamps	2-54 2 Lamps 54 Watts F54-T5H0 Lamp Not Included 3-32 3 Lamps 32 Watts F32-T8 Lamp Not Included 3-54 3 Lamps 54 Watts F54-T5H0	2-54 2 Lamps 54 Watts F54-T5HO Lamp Not Included 3-32 3 Lamps 32 Watts F32-T8 Lamp Not Included 3-54 3 Lamps 54 Watts F54-T5HO	2-54 2 Lamps 54 Watts F54-T5HO Lamp Not Included 3-32 3 Lamps 32 Watts F32-T8 Lamp Not Included 3-54 3 Lamps 54 Watts F54-T5HO