



## FIXTURE SPECIFICATIONS

### INTENDED USE

The **12400-6 Architectural LED Surface Mount Direct Down Light** is designed for higher wattage capabilities and indoor and outdoor use. The 12400-6 is an ideal solution for commercial areas and displays.

### FEATURES

- H 8.5" x Dia 5.75"**
- Construction:** Premium Steel, Aluminum, and Zinc Alloy  
Corrosion Resistant
- Beam Angle:** 120°
- Voltage:** 120V (50/60 Hz)
- Wattage:** 10W
- Operating Frequency:** 120 Hz
- CRI:** 80
- Life:** 50,000 Hours (L70)
- Flame Rating:** 5VA
- Listings:** UL Listed for Wet Locations
- Warranty:** 5 years carefree for parts and components (labor not included)



## ORDERING INFORMATION Example: (12400-6-27K-GR)

Model	Color Temp <sup>1</sup>	Finish	Options
<b>12400-6</b>	<b>27K</b> 2700K   864 Lumens	<b>WH</b> White	<b>AG</b> Anti-Glare
	<b>30K</b> 3000K   960 Lumens		
	<b>35K</b> 3500K   1120 Lumens	<b>BK</b> Black	
	<b>40K</b> 4000K   1280 Lumens	<b>GY</b> Grey	
		<b>BR</b> Bronze	
		<b>SA</b> Satin Aluminum	
		<b>GR</b> Green	
		<b>SB</b> Satin Brass	
		<b>AB</b> Antique Brass	
		<b>R</b> Rust	

<sup>1</sup>90 CRI Available on Request