

Project: _____ Type: _____



FEATURES

The BSW208 is a linear LED luminaire for outdoor applications. The surface mount 2" wide by 3" tall extrusion is fitted with a flush, frosted lens and machined aluminum end caps. Each fixture is paired with a remote mounted wet location 0-10V dimming or non-dimming driver and housing.

SPECIFICATIONS

Fixture constructed of an extruded aluminum housing, extruded, frosted acrylic lens and machined aluminum end caps

Standard finishes as shown below

Available for surface or wall mounting in nominal lengths of 2'-8' single fixtures and continuous runs

Fixtures wired with 10' low voltage leads

Included remote 120-277V wet location driver offered with 0-10V dimming or non-dim and surface mount aluminum enclosure

Standard outputs are 345, 690 and 925 lumens per foot


LEDs available in 2700K, 3000K, 3500K and 4000K, within a 3 step MacAdam ellipse, all with 80+ CRI typical

Life: 50,000 hours L₇₀

Limited five year warranty

UL and C-UL listed for wet locations

SECTION



[GET A QUOTE >](#)

PERFORMANCE

NOMINAL LENGTH	OUTPUT	LUMENS/ft.	WATTS/ft.	LUMINAIRE LUMENS	EFFICACY (LPW)
4'	L: low	345	4.0	1382	87
	R: regular	690	8.0	2759	86
	H: high	925	10.7	3694	87



Note: All data reflects fixture with 3500K LEDs

BSW208 -

NOMINAL FIXTURE LENGTH*
 2: 24-5/8"
 3: 36-5/8"
 4: 48-5/8"
 5: 60-5/8"
 6: 72-5/8"
 7: 84-5/8"
 8: 96-5/8"

CORRELATED COLOR TEMPERATURE
 27: 2700K-80+ CRI
 30: 3000K-80+ CRI
 35: 3500K-80+ CRI
 40: 4000K-80+ CRI

DRIVER [remote]
 RN: non-dimming
 RD: 0-10V dimming, 5%

LIGHT OUTPUT (lumens per foot)
 L: low - 345
 R: regular - 690
 H: high - 925



MOUNT
 SM: surface mount
 WD: wall mount-direct
 WI: wall mount-indirect

RUN CONFIGURATION
 SN: single
 ST: starter
 AD: adder
 TR: terminator

FINISH
 AW: architectural white (semi-matte)
 WH: white (semi-gloss)
 BL: black (semi-matte)
 MB: matte black
 ESS: environmental satin silver
 BZ: bronze
 PR: primer
 CF: consult factory for custom finish

Note: Each fixture includes a remote driver matched for fixture length and light output
 * Actual dimension dependent on run configuration

MOUNTING

	ORDERING CODE	DESCRIPTION
	SM	<p>SURFACE MOUNT</p> <ul style="list-style-type: none"> Use appropriate fastener through $\varnothing 3/16"$ holes in housing
	WD	<p>WALL MOUNT - DIRECT ORIENTATION</p> <p>Mounting option includes:</p> <ul style="list-style-type: none"> 1-7/8" H x 4-1/2" W aluminum bracket projects the fixture housing 3/4:" from the wall surface
	WI	<p>WALL MOUNT - INDIRECT ORIENTATION</p> <p>Mounting option includes:</p> <ul style="list-style-type: none"> 1-7/8" H x 4-1/2" W aluminum bracket projects the fixture housing 3/4:" from the wall surface

EPA CALCULATIONS

LENGTH ORDERING CODE	EPA
2	0.99 ft ²
3	1.46 ft ²
4	1.94 ft ²
5	2.42 ft ²
6	2.89 ft ²
7	3.36 ft ²
8	3.84 ft ²