



GENERAL SPECIFICATION

Housing: Round metal frame consisting of modules combined together for electrical and mechanical connection. Bubble 3D supplied in the following diameters: 1000mm (39.4"), 1800mm (70.9") and 2800mm (110.0").

Diffusers: Injection molded, UV stabilized, opal polycarbonate. Diffusers are sectional with subtle but visible seams. Bubble 1000, 3 diffusers; Bubble 1800, 8 diffusers and Bubble 2800, 16 diffusers.

Drivers: Luminaires supplied with remote electronic drivers, 120/277V. Connection of the power cords (approx 6) to the remote drivers by others.

Power cables: Luminaires, supplied with 13.5m/35' of cable. Cables can be extended to a maximum overall distance of 20m/64'. Custom cable lengths can be supplied to special order.

Mechanical: Luminaires mount directly over a junction box.

Finish: White RAL 9003.

Approvals: ETL.






A SPECIFY LAMP/LUMINAIRE TYPE

ADJUSTABLE PENDANT Complete with suspension and power cable (3000K lamps included).

 Code:
 Lamp:
 Weight:

 BCBT500P
 LED 555W + 328W + 170W, 3000K 82900lm (total), 2 x remote power supplies included.
 130kg/286.6lb

Composed of Bubble 2800 + Bubble 1800 + Bubble 1000 with suspended cables and canopy. Positions fixed as per drawing (triple circuit).




LOW PROFILE PENDANT Complete with suspension and power cable (3000K lamps included).

 Code:
 Lamp:
 Weight:

 BCBT501LP
 LED 555W + 328W + 170W, 3000K 82900lm (total), 2 x remote power supplies included.
 130kg/286.6lb

Composed of Bubble 2800 + Bubble 1800 + Bubble 1000 with suspended cables and canopy. Positions fixed as per drawing (Triple circuit).



B SPECIFY ACCESSORIES (REQUIRED)

150A031VE Umbrella tool for assembly/installation of Bubble 2800. Retains structural integrity during the installation process (only one required).

