# BUBBLE RGB ¥WEB PIN™ 260



## **GENERAL SPECIFICATION**

Housing: Round metal frame consisting of modules combined together for electrical and mechanical connection. Bubbles supplied in the following diameters: 600mm (23.6") 1000mm (39.4"), 1800mm (70.9") and 2800mm (110.0").

Diffusers: Injection molded, UV stabilized, opal polycarbonate. Diffusers are sectional with subtle but visible seams. Bubble 600, 3 diffusers; Bubble 1000, 3 diffusers; Bubble 1800, 8 diffusers and Bubble 2800, 16 diffusers.

Drivers/power supplies: Luminaires supplied with electronic drivers/DMX interfaces, 120/277V.

Power cables: Luminaires supplied with 7.8m/20' of cable. Cables can be extended to a maximum overall distance of 20m/64'. Custom cable lengths can be supplied to special order.

RGB control: Luminaires require a DMX controller by others. Mechanical: Luminaires mount directly over a junction box.

Finish: White RAL 9003.

Approvals: ETL.





# DIAMETER: 600/1000/1800

#### A SPECIFY LAMP/LUMINAIRE TYPE

Code:	Lamp:	Diameter (A):	Diameter (B):	Depth (D):	Weight:
D15SD163AE	45W LED RGB	600mm/23.6"	440mm/17.3"	191mm/7.5"	8.1kg/17.9lbs
D15SD164AE	80W LED RGB	1000mm/39.4"	800mm/31.5"	241mm/9.5"	16.1kg/35.5lbs
D15SD165AE	156W LED RGB	1800mm/70.9"	1600mm/63.0"	241mm/9.5"	33.0kg/72.8lbs

#### B SPECIFY POWER SUPPLY AND ACCESSORIES

#### Bubble Emotion integral power supply including DMX interface (complete with larger diameter canopy)

Canopy with power supply and DMX interface for Bubble 600 BCDMX10/IN Canopy with power supply and DMX interface for Bubble 1000 BCDMX18/IN Canopy with power supply and DMX interface for Bubble 1800

#### Bubble Emotion remote power supply including DMX interface (specify mounting canopy from bubble accessories as a separate line item)

BCDMX6/R Remote power supply with DMX interface for Bubble 600 BCDMX10/R Remote power supply with DMX interface for Bubble 1000 BCDMX18/R Remote power supply with DMX interface for Bubble 1800

#### Bubble Emotion accessories (for luminaires with remote power supplies only)

Ceiling canopy for installation to load bearing ceilings (max 32kg/70lbs) MEC1745AE

for Bubble 600 and Bubble 1000.

Ceiling canopy for installation to load bearing ceilings (max 100kg/220lbs) MEC2112AE

for Bubble 1800


Ceiling canopy for installation into false ceilings MEC1823AE

or similar (cables are anchored to the load bearing ceiling).


#### Surface mounting kits for remote power supply.

**BCLED6/SK** Surface mounting kit for Bubble 600 BCLED10/SK Surface mounting kit for Bubble 1000 BCLED18/SK Surface mounting kit for Bubble 1800


#### Notes: DMX CONTROLLERS BY OTHERS










BCDMX6/R BCDMX10/R



BCDMX18/R











# DIAMETER: 2800

### A SPECIFY LAMP/LUMINAIRE TYPE

LOW PROFILE PENDANT Luminaire complete with 8 suspension cables connected to the central joint for ceiling mounting.

Code: Lamp: Weight: BCBE28LPRC 264W LED RGB, remote power supply with DMX interface 63kg/138.9lb







ADJUSTABLE PENDANT Luminaire complete with 8 cables connected to the central joint and 4 adjustable cables for ceiling mounting.


 Code:
 Lamp:
 Weight:

 BCBE28PIC
 264W LED RGB, integral power supply with DMX interface
 75kg/165.3lb

 BCBE28PRC
 264W LED RGB, remote power supply with DMX interface
 67kg/147.7lb










# DIAMETER: 2800


CEILING MOUNTED Luminaire complete with 8 suspension cables L=2000mm/79".


Code: Lamp:

BCBE28CMRC 264W LED RGB, integral power supply with DMX interface BCBE28CMRC 264W LED RGB, remote power supply with DMX interface

**Weight:** 74kg/163.1lb 66kg/145.5lb







## B SPECIFY ACCESSORIES (REQUIRED)

**150A031VE** Umbrella tool for assembly/installation of Bubble 2800. Retains structural integrity during the installation process (only one required).

