

SOLID STATE AREA LIGHTING

8456 SERIES-LED

SPECIFICATIONS

HOUSING

Heavy wall cast aluminum (A356 alloy; < 0.2% copper) construction. Powder coated for use in concrete. Two (2) 3/4" NPT conduit entries provided at bottom of Splice Compartment.

LENS FRAME

Cast aluminum (A356 alloy; < 0.2% copper) construction in louvered frame or open frame configurations.

LENS

LOUVERED LENS FRAME: 3/16" tempered glass, frosted (ALF) or prismatic (ALP).

OPEN LENS FRAME: 3/16" tempered glass, frosted (NLF) or prismatic (NLP).

LED MODULE

Array of multiple LED Tubes fastened to a retaining plate. Each LED Tube consists of circuit board populated with a multiple of LED's and is mechanically fastened to a radial aluminum heat sink. An acrylic Lens and end cap protects the LED Tube's internal components.

LED EMITTERS

High Output LED's are driven at 350mA for nominal 1 Watt output each. LED's are available in standard Neutral White (4000K), or optional Cool White (5000K) or Warm White (3000K). Consult Factory for other LED options.

LED DRIVER



UL and CUL recognized High Power Factor, Constant Current LED drivers operate on input voltages from 120-277VAC, 50/60hz. Consult Factory for 347-480VAC. Driver is mechanically fastened to a retaining bracket. Main power quick disconnect provided. Driver has a minimum 4KV of internal surge protection, 10KV & 20KV Surge Protector optional. Dimming and High-Low Driver options available.

FINISH

Polyester powder coat incorporates four step iron phosphate process to pretreat metal surface for maximum adhesion. Top coat is baked at 400°F for maximum hardness and exterior durability.




PROJECT NAME: _____

PROJECT TYPE: _____



8456-AL

PATENT PENDING



8456-NL*

*Shown with -NLP Face Option

PATENT PENDING




2014064


8456 SERIES - LED

S P E C I F I C A T I O N S

OPTICAL CONFIGURATIONS




LED MODULE




8456-AL-LED
Louvered Face

20 LED



LED MODULE







8456-NL-LED
Open Face

20 LED

Spec/Order Example: 8456-ALP/20LED-NW/120/RAL-9003-S

S P E C / O R D E R I N G I N F O R M A T I O N

MODEL	# of LED's	COLOR TEMP - CCT	VOLTAGE	FINISH	OPTIONS
MODEL	LED	FINISH	OPTIONS		
<input type="checkbox"/> 8456 - ALF  Louvered Face Frosted Glass	<input type="checkbox"/> 20LED (23 Watts)	<input type="checkbox"/> NW (4000K)* *STANDARD <input type="checkbox"/> CW (5000K) <input type="checkbox"/> WW (3000K) OTHER LED COLORS AVAILABLE CONSULT FACTORY	<input type="checkbox"/> 120 <input type="checkbox"/> 208 <input type="checkbox"/> 240 <input type="checkbox"/> 277	STANDARD TEXTURED FINISH <input type="checkbox"/> BLACK RAL-9005-T <input type="checkbox"/> WHITE RAL-9003-T <input type="checkbox"/> GREY RAL-7004-T <input type="checkbox"/> DARK BRONZE RAL-8019-T <input type="checkbox"/> GREEN RAL-6005-T FOR SMOOTH FINISH REPLACE SUFFIX "-T" WITH SUFFIX "-S" (EXAMPLE: RAL-9005-S)	<input type="checkbox"/> 10KV SURGE PROTECTOR. 10SP <input type="checkbox"/> SINGLE FUSED (120V., 277V) SF <input type="checkbox"/> DOUBLE FUSE (208V., 240V) DF
<input type="checkbox"/> 8456 - ALP  Louvered face Prismatic Glass					
<input type="checkbox"/> 8456 - NLF  Open Face Frosted Glass					
<input type="checkbox"/> 8456 - NLP  Open Face Prismatic Glass					
	1 - CONSULT FACTORY FOR 347V APPLICATION			CONSULT FACTORY FOR CUSTOM COLORS	