



2.37

60.198 mm

21.0

533.4 mm

42.0

1066.8 mm

X-TREME PENDANT



OA SERIES / 105 WATT MAX LED

XT4804LEDOA

APPLICATION

X-treme LED pendant for functional area lighting or decorative accent. FEATURES

Delivers a range of 4800 lumens. Three available lens distributions from 50° to 90°. May be surface or cable mounted. Passive LED heatsinks with integral LED drivers are ease to access for maintenance or up-grade.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. A wide variety of standard and custom finishes are available. All exposed materials are chromate pretreated to resist corrosion.

ELECTRONICS

LED system features high brightness white LED's. 3 step MacAdam Ellipses binning. Standard CRI: 85+. Higher CRI are available; consult factory. Variety of electronic 120v/277v and dimming drivers.

CONSTRUCTION

Fixtures are constructed of machined and fabricated aluminum extrusion and finished to specification. Lens material reduces image of LED emitters. CODE COMPLIANCE

ARRA Compliant. ETL/UL/CSA listed for damp locations. LM79/LM80/TM21 data available. Manufactured and tested to UL standards No. 1598/8750.

SERIES	LED	KELVIN	BALLAST	OPTIONS	MOUNTING	FINISH	LENS
XT4804	LEDOA 105W 4895 Lumens* *Nominal Delivered Lumens 35K-E1-FO90	30K-3000° K 35K-3500° K 40K-4000° K	E1-Electronic, 120v E2-Electronic, 277v DS101-Spectrum 0-10v Dimming, 120v to 10% DS102-Spectrum 0-10v Dimming, 277v to 10%	2CIR-2 Circuit	PM4X*-4X Pendant Mount CD4X*-4 Cable from Mounting	MW-Matte White MB-Matte Black GW-Gloss White GB-Gloss Black BZ-Bronze OB-Oil Rubbed Bronze PT-Platinum SI-Silver GA-Galvanized BA-Brushed Aluminum CH-Charcoal GH-Graphite AM-Anodic Malachite SN-Sun Gold BL-Blue Streak RD-Red Baron CO-Copper Metallic CC-Custom Color	FO50-50° Distribution Lens FO70-70° Distribution Lens FO90-90° Distribution Lens

EXAMPLE: XT4804LEDOA105WE1/CD4X36MWFO90

Dimensions shown are nominal. Spectrum Lighting is continually improving products and reserves the right to make changes that will not after performance or appearance with or without written notice.

48.0

1219.2 mm

4.75

120.65 mm



PROJECT: TYPE: CAT. NO.:



WWW.SPECLIGHT.COM • 994 JEFFERSON STREET, FALL RIVER, MA 02721 • 508.678.2303 FAX 508.678.2260