Quantity:

Alcon 11147 Outdoor LED Half Moon Wall Pack | Wattage Selectable



SPECIFICATION SHEET

Project Name:

INTENDED USE

Assembled in the USA, our wet-location half sphere wall sconce is available as either a downlight with a wattage selectable switch or a down and uplight at 40W for each down and uplight. Ideal for Commercial or residential applications such as exterior walls, parking areas, entrances, underpasses, loading docks and recreation areas.

Type:

FEATURES

Construction: Die-cast aluminum housing with UV stabilized

powder coated finish.

Lens: Impact resistant tempered clear glass lens Mounting: Wall mount (mount plate included)

Finish: Dark Bronze (RAL#7022) Voltage: 120V-277V, 50/60Hz

Operating Temperature: -40°F (-40°C) ~ 104°F (40°C)

CRI: 70+ Standard Life: 50,000 Hours

Warranty: 5 years Carefree for parts & components

(Labor not included)

Listings: cULus, Suitable for Wet Location, Assembled in the

USA, DLC Premium



DI - Direct & Indirect Option















Direct Only Selectable Wattage Lumen							
Wattage	Lumens (30K)	Lumens (40K)	Lumens (50K)				
25W	2983L	3137L	3077L				
45W	5419L	5857L	5535L				
65W	7855L	8568L	7992L				

Ordering Information: Example: (11147-D-F-7-30K-DS)

Direct & Indirect 40 Watts 6056 Lumen Wide Throw 80+ CRI 4000K 50K 50K 50OOK 8EM 8W Emergency Battery Backup CEM 10W EM Pack for Cold Weather	Model	LED Wattage Lumen	Beam Spread	CRI	Color Temp	Options
SP 140W and 6056L for both up and downlight 10Kv Surge Protector	11147	Direct Only Wattage & Lumen Selectable DI	Forward Throw W	70+ CRI 8	3000K 40K 4000K 50K	Daylight sensor OS/DS Occupancy Sensor with Daylight sensor Adjustable via DIP switch OS/DS-R Remote control for OS/DS 8EM 8W Emergency Battery Backup CEM 10W EM Pack for Cold Weather (-20°C ~ 55°C) SP

2 Only available for Direct only fixture

Wide Throw 11147-D-W




Forward Throw 11147-D-F









Up & Down **11147-DI-F**



