

Project Name: _____ Type: _____ Quantity: _____

INTENDED USE

The outdoor flexible LED light strip is a high-performance fixture that replaces neon lighting. The flexible design allows for smooth, continuous illumination, bending around tight curves without damage. The silicone housing provides durability, with factory-sealed connectors for secure installation. Designed to bend vertically around contours without damage, this versatile strip is available in multiple color temperatures and customizable lengths, allowing for versatile ambiance control in commercial, residential, pool, spa, façade, and perimeter lighting applications.



FEATURES

- Construction:** Silicone
- Lens:** Flat
- Bend Direction:** Vertical
- Beam angle:** 160°
- CRI:** 80+
- Voltage:** 120-277V
- External Driver:** 0-10V, MLV, ELV, and TRIAC (IP65 Rated)
- Power Consumption:** 7 watt per ft.
- Lumen Output:** 305 lumens per ft.
- Max run:** Continuous run length up to 16.4 ft cuttable every 4.92 in
- Operating Temperature:** -40°F ~131°F
- Storage Temperature:** -40°F ~140°F
- Life:** 50,000 Hours
- Listing:** IP65, UV and Flame Resistant
- Warranty:** 5 years carefree for parts & components (Labor not included).



SPEC
.....
GRADE

5
YEAR
WARRANTY

WET

IP65

FIRE RATED



UV
RESISTANT

ORDERING INFORMATION Example:

Model	Color Temp	Length	End Power Feed Cord Length	Mounting Channels Option
11259	27K 2700K	CODE Please refer to pages 3 for exact lengths with corresponding ordering codes	3* 3 ft.	39AL 39" Aluminum
	30K 3000K		10 10 ft.	
	40K 4000K		15 15 ft.	
	50K 5000K		30 30 ft.	
			50 50 ft.	

* Standard


DIMENSIONS




* LED strip only bends vertically along light surface. Do NOT bend more than the indicated minimum bend diameter (shown above). Doing so will damage the LED strip.

POWER FEED

End Power Feed
Cord available in 3/10/15/30/50 ft.





End Cap



MOUNTING ACCESSORIES


Aluminum Profile
39AL



¹For wall wash applications
²Two Standard Tilting brackets are included. Further information in Pg. 3.

EXTERNAL DRIVER

Driver	Dimensions
4N1-30W-24V	6.50" x 3.72" x 1.57"
4N1-60W-24V	7.40" x 3.72" x 1.57"
4N1-96W-24V	8.66" x 3.72" x 1.57"
4N1-150W-24V	10.24" x 4.13" x 1.77"
4N1-200W-24V	10.24" x 4.13" x 1.77"
4N1-300W-24V	10.94" x 4.33" x 1.77"



CUTTING LENGTH CODES

Cuts are made every 4.92". Please refer to table below to determine actual lengths once LED is cut versus actual lengths required or specified.

Total Length Calculation = order code length + end feed option length

Example: 55.22" total length = Order Code 11 (54.12") + (1.1") End Feed

Optional lead wire lengths available: 3ft., 10ft., 15ft., 30ft., 50ft.

Code	Inches	Code	Inches
1	4.92	21	103.32
2	9.84	22	108.24
3	14.76	23	113.16
4	19.68	24	118.08
5	24.6	25	123
6	29.52	26	127.92
7	34.44	27	132.84
8	39.36	28	137.76
9	44.28	29	142.68
10	49.2	30	147.6
11	54.12	31	152.52
12	59.04	32	157.44
13	63.96	33	162.36
14	68.88	34	167.28
15	73.8	35	172.2
16	78.72	36	177.12
17	83.64	37	182.04
18	88.56	38	186.96
19	93.48	39	191.88
20	98.4	40	196.8

COMPATIBLE DIMMERS

			
0-10 V	2100 2101 2102	Diva DTVV	IP-710-DL

COLOR TEMPERATURE GUIDE

<p>2700K</p> <p>WARM WHITE</p> <p>friendly personal intimate</p> <p>HOMES LIBRARIES RESTAURANTS</p> <p>✓</p>	<p>3000K</p> <p>SOFT WHITE GLOW</p> <p>soft warm pleasing</p> <p>HOMES HOTEL ROOMS LOBBIES RETAIL STORES</p> <p>✓</p>	<p>3500K</p> <p>NEUTRAL GLOW</p> <p>sociable inviting non-threatening</p> <p>EXECUTIVE OFFICES RECEPTION AREAS SUPERMARKETS</p> <p>X</p>	<p>4000K</p> <p>COOL WHITE GLOW</p> <p>neat clean efficient</p> <p>OFFICES CLASSROOMS MASS MERCHANTISERS SHOWROOMS</p> <p>✓</p>	<p>5000K</p> <p>DAYLIGHT GLOW</p> <p>bright cool alert</p> <p>GRAPHICS INDUSTRY HOSPITALS GALLERIES BEAUTY SALONS</p> <p>✓</p>
---	--	---	--	---