


Project Name: _____ Type: _____ Quantity: _____

INTENDED USE

Featuring an elegant and original design, this large, architectural-grade LED half circle pendant affords powerful downlighting and uplighting. Designed with hospitality, residential and commercial interiors in mind, our light comes in extruded aluminum outer housing with a glare-free reflector. The distinctive light includes adjustable aircraft cables for hanging.

FEATURES


- Construction:** Extruded aluminum outer housing
Adjustable power cord and AC cables with push button grippers are standard
- Lens:** White frosted acrylic diffuser
- Reflector:** Glare-free, one piece, heavy gauge aluminum
- Dimensions:** Width 1.10" x Depth 2.20"
- Mounting:** All standard J-boxes
- Remote Canopy:** 3.80" D x 0.45" H
- Pendant:** 8' adjustable aircraft cables/power cord included
(Custom length available, consult MFG)
- Voltage:** 120/277VAC
- Dimming:** 0-10V (100-1%) for static white options
- CRI:** 90+
- External Emergency Back-up Battery:** 10 Watts for 90 Minutes
- Listings:** ETL listed per UL and CSA standards, Made in USA, Buy American Act (BAA) compliant



Linear Length Options

- L2** – 2 ft. (23.65")
- L3** – 3 ft. (35.00")
- L4** – 4 ft. (46.40")
- L5** – 5 ft. (57.75")
- L6** – 6 ft. (69.15")
- L8** – 8 ft. (91.90")

Circle Shape Options




ORDERING INFORMATION Example: 12258-C-2-90-2-L4-2-30K-SL-WH


Model	Circle Shapes Radius Wattage Lumens	Linear Length Wattage Lumens	Optics	Color Temperature	Finish ²	Options
12258	90-17	(Blank)	Blank ¹	30K	WH	EM10X ³
	90° 17 in. 24 Watts 2045 lm	Circle Shape Only	Direct Downlight	3000K	White	10W External Emergency Back-up Battery
	90-22	L2	DI	35K	BK	AB ⁴
	90° 22.55 in. 28 Watts 2100 lm	2 Foot 20 Watts 1732 Lumens	Direct / Indirect	3500K	Black	AB Switching
	90-37	L3		40K	SL	XX
	90° 37 in. 49 Watts 4100 lm	3 Foot 30 Watts 2585 Lumens		4000K	Silver	Custom AC Cable/Power Cord (25' Max)
	120-17	L4		RGBW		DMX-W-WIFI ⁵
	120° 17.55 in. 30 Watts 2700 lm	4 Foot 40 Watts 3465 Lumens		RGB+ W (3500K)		DMX Wall Control (White) + WiFi
	120-22	L5				DMX-B-WIFI ⁵
	120° 22 in. 43 Watts 3630 lm	5 Foot 50 Watts 4317 Lumens				DMX Wall Control (Black) + WiFi
	120-40	L6				
	120° 40 in. 80 Watts 5460 lm	6 Foot 60 Watts 5170 Lumens				
180-17	L8					
180° 17 in. 44 Watts 4100 lm	8 Foot 80 Watts 6930 Lumens					
180-22	Lx					
180° 22.55 in. 56 Watts 4200 lm	Custom Length					
180-37						
180° 37 in. 98 Watts 8200 lm						

¹ This option reduces mA, watts, and delivered lumens by half.
² Canopy and cord finish will match the fixture's finish.
³ Designed for remote installation, with a red indicator light and test switch housed in a convenient ceiling-mounted box. Extends remote driver length to 36 inches.
⁴ Direct and indirect LEDs may be wired separately. The quantity of drivers, quantity of feed points, and size of driver box (36")* may increase.
⁵ See further information on page 3.


Alcon 12258 Half Circle 180° LED Pendant Uplight and Downlight



Cross Section




Remote Driver Mounting



Remote Driver Canopy
3.80" D x 0.45" H




End Caps
Included



Joiner


EXAMPLE OF THE DESIGNS MADE POSSIBLE WITH THE CONTOUR




COMPATIBLE DIMMERS FOR STATIC WHITE

	ALCON LIGHTING	LUTRON	LEVITON
0-10 V	2100 2101 2102	Diva DDTV	IP-710-DL

RGB DMX CONTROLS



DMX-W-WIFI
DMX Wall Control (White) + WiFi



DMX-B-WIFI
DMX Wall Control (Black) + WiFi

COLOR TEMPERATURE GUIDE

2700K	3000K	3500K	4000K	5000K
WARM WHITE	SOFT WHITE GLOW	NEUTRAL GLOW	COOL WHITE GLOW	DAYLIGHT GLOW
friendly personal intimate	soft warm pleasing	sociable inviting non-threatening	neat clean efficient	bright cool alert
HOMES LIBRARIES RESTAURANTS	HOMES HOTEL ROOMS LOBBIES RETAIL STORES	EXECUTIVE OFFICES RECEPTION AREAS SUPERMARKETS	OFFICES CLASSROOMS MASS MERCHANDISERS SHOWROOMS	GRAPHICS INDUSTRY HOSPITALS GALLERIES BEAUTY SALONS
X	✓	✓	✓	X