

FIXTURE SPECIFICATIONS

INTENDED USE

Built with a Black aluminum housing, our 2x2 LED recessed fixture features sound absorbing acoustic felt ideal for spaces that will benefit from reduced noise. The 11166 can be ordered in a variety of ways: as a non-lit, acoustic felt only product that drops from the ceiling, a LED lit product with acoustic felts that is recessed into the ceiling, an a LED only product. This product can be customized in a number of ways to suit open offices, lobbies and reception areas and corridors, and other commercial interiors.

PRODUCT FAMILY

11166: Non-Lit Sound Absorbing Acoustics Fixture
11166-P: LED Pendant with Sound Absorbing Acoustics
11166-R: LED Recessed Flat Panel with Sound Absorbing Acoustics

FEATURES

Wattage & Color Temperature Switch: Features Field adjustable Wattage and Color temp switch capable of switching wattages from 25 to 40 Watts and color temperatures of 35K to 50K.

Lens: Frosted acrylic diffuser

Voltage: 120–277V

Life: 50,000 Hours

Warranty: 5 Years carefree for parts & components (labor not included)

Listings: cULus, DLC, ARRA compliant, BAA compliant



LED	Watts	Color Temp	Lumen Output
Wattage & Color Temperature Selectable	40W	3500K	3828lm
		4000K	3828lm
		5000K	3897lm
	30W	3500K	2949lm
		4000K	2975lm
		5000K	3001lm
	25W	3500K	2523lm
		4000K	2544lm
		5000K	2566lm



ORDERING INFORMATION Example: (11166-AD-2-RT-010)

Model	Size	Mounting	Dimming	Options
11166-AD 1	1" Acrylic Drop 2	RT Recessed T-bar	010 Standard 0-10V Dimming (120–277V)	OS Bi-Level Occupancy Sensor
	2" Acrylic Drop 4	FK Flange Kit for Hard Ceiling	ELV ELV Dimming (120–277V)	EM8 8W Emergency Back-Up Battery
	4" Acrylic Drop 6		TRIAC TRIAC Dimming (120V Only)	EM16 16W Emergency Back-Up Battery
	6" Acrylic Drop			EM20 20W Emergency Back-Up Battery

11166 (\$ \$¥ € £) 1 \$ 20 4A ©