

**Project Name:** 

Type:

Quantity:

SHOP NOW

#### **FIXTURE SPECIFICATIONS**

#### INTENDED USE

The specification grade Edge Lit LED Flat Panel light fixture integrates the latest in LED technology with a low profile design not previously available with conventional light fixtures. New LED lens technology channels the light emitted by the LED's on the side of the fixture and directs the light downward creating uniform light distribution without hot spots, flicker or glare. The streamlined design of these LED flat panels combined with easy-to-install mounting brackets and safety earthquake clips enables simple installation in both residential and commercial buildings providing 80% in energy savings and 100,000 hours of reliable light.



**Design:** White framed edge, t-bar drop ceiling, troffer

replacement

**Mounting:** 66" Aircraft Cable Pendant and mounting frame

sold separately

**Field Adjustable Color Temperature:** 3500K/4000K/5000K

Voltage: 120-277VAC

**Operating Temperature: -**4°F to 113°F **Dimming:** 0-10V (100-10% dimming)

CRI: 80+


**LED Life:** 100,000 Hours

Warranty: 5 Years Carefree for Parts & Components


(labor not included)

**Listings:** cULus, DLC, Assembled in the USA





**Surface Mounting Frame Kit** 













# ORDERING INFORMATION Example: (14052-P-14)

Model	Туре	Size	Options
14052	<b>P</b> Pendant	<b>14</b> 1' x 4'	EM15 EM Battery Backup 15W  2430L EM25 EM Battery Backup
	<b>R</b> Recessed T-Bar	<b>22</b> Bar 2' x 2'	
	<b>S</b> Surface	<b>24</b> 2' x 4'	25W  4050L


#### Wattage | Lumen Chart

LED Watts	Lumen Output 3500   4000   5000K			
40W	4400lm   4440lm   4480lm			
30W	3390lm   3420lm   3450lm			
25W	2900lm   2925lm   2950lm			
50W	5500lm   5550lm   5600lm			
40W	4520lm   4560lm   4600lm			
30W	3480lm   3510lm   3540lm			
	40W 30W 25W 50W 40W			



# **DIMENSIONS**

Flat Panel



<u>1'x4'</u>

Length: 47-3/4" Width: 11-7/8" Depth: 1-5/8"


2'x2'

Length: 23-3/4" Width: 23-3/4" Depth: 1-5/8"

2'x4'

Length: 47-3/4" Width: 23-3/4" Depth: 1-5/8"

# Flat Panel with Surface Mounting Kit



## 1'x4'

Length: 47-15/16" Width: 11-31/32" Depth: 2-13/16"

\* Depth increased up to 5.2" with EM option.

## 2'x2'

Length: 23-7/8" Width: 23-7/8" Depth: 2-13/16"

\* Depth increased up to 5.2" with EM option.

# 2'x4'

Length: 47-15/16" Width: 23-7/8" Depth: 2-13/16"

\* Depth increased up to 5.2" with EM option.