

FIXTURE SPECIFICATIONS

INTENDED USE


The specifications grade Deep Dome Architectural LED High Bay Direct Down Light Fixture has been designed to offer high light output and withstand harsh industrial conditions. The Deep Dome provides high CRI increasing the light quality of a space and improving visibility, thus reducing the chance of accidents.

DETAILS

Model Number: 12232
 D 47.25" (1.2m) x H 1.5" (.4m)
 Weight: 32.12 lbs
 Finish: Silver

FEATURES

Construction: Sleek Design with Large Reflective Surface for Smooth Down Lit Glow
 Voltage: 120V/277V
 Wattage: 0-10V
 Dimming: 6501m
 Life: 50,000 Hours
 CRI: 75
 Warranty: 1 Year carefree for parts & components (Labor not included)
 Listings: ETL Listed



Alcon Lighting 15201 Architectural LED Pendant Dome Light



ORDERING INFORMATION Example: (15201-8-15W-30K-WH-WH-48ACB)

Model	Size	Wattage Lumens	Color Temp	Exterior Finish	Interior Finish	Mounting
15201	8 8"	15W	30K 3000K	WH White	WH White	48ACB 48" Black Finish Cord
	10 10"	15 Watts 1650 lms	40K 4000K	BK Black	BK Black	48ACW 48" White Finish Cord
	12 12"	20W¹	60K² 6000K	RD Red	RD Red	ST12 12" L x 1/2" Stem
	16 16"	20 Watts 2400 lms		BL Blue	BL Blue	ST18 18" L x 1/2" Stem
	20 20"	30W¹		GR Green	GR Green	ST24 24" L x 1/2" Stem
		30 Watts 3600 lms		YL Yellow	YL Yellow	ST36 36" L x 1/2" Stem
		40W¹		GV Galvanized	GV³ Galvanized	ST48 48" L x 1/2" Stem
		40 Watts 4800 lms		CP Copper	CP Copper	
				SN Satin Nickel	SN Satin Nickel	

¹ Only Available in 30K & 40K

² Only Available with 15W

³ Only Available with Galvanized Exterior Finish