

Project Name: _____ Type: ____ Quantity: ____ Shop Now

FIXTURE SPECIFICATIONS

INTENDED USE

With a frosted round lens and die-cast aluminum heat sink housing, the Darwin 15230 is ideal for warehouse, gymnasium and other mid to high-ceiling applications where high output LED lighting is desired.

FEATURES

Construction: Die cast aluminum heat sink housing.

Spun .063 aluminum reflector.

Lens: Frosted round lens, safe for food service

applications

LED: Nichia Corp.

Driver: 0–10V 5-wire 1% dimming. Input Voltage: 120/277V, 50/60Hz

Emergency Back Up: OW optional emergency back up

battery available.

Listings: cUL listed for damp locations, Made in the

USA











ORDERING INFORMATION Example:

Model	Exterior Finish	Interior Finish	Color Temp	Wattage Lumens
15230	BK	WH	30K	5L
	Black	White	3000K	32 Watts 5000 lms
	WH	GD	35K	10L
	White	Gold	3500K	64 Watts 10000 lms
	SL	AN	40K	15L
	Silver	Anodized	4000K	96 Watts 15000 lms

S	Mounting	Canopy Color	Cord Color	Options
ıs	AC96 96" Adjustable	BK Black	BK Black	EM10 10W Emergency Back up Battery
ns	Aircraft Cable ACXX	SL Silver	G Gray	(90 minutes)
ns	Custom Adjustable Aircraft Cable (Replace XX with Length in Inches)	WH White	WH White	
	Remote Driver			
	AC96			
	96" Adjustable			

ACXX

Custom Adjustable Aircraft Cable (Replace XX with Length in Inches)

ST24

24" Stem

ST36

36" Stem

ST48

48" Stem

STXX

Custom Stem (Replace XX with Length in Inches)



COMPATIBLE DIMMERS

	LIGHTING	%LUTRON	LEVITON _®
	<u>2100</u>	Diva DVTV	IP-710-DL
0-10 V	<u>2101</u>		
	2102		

