SPECIFICATION SHEET



Project Name:

Quantity: Type:

Shop Now

FIXTURE SPECIFICATIONS

INTENDED USE

The specification grade Alcon Lighting 15235 Melbourne Round Cone LED High Bay Commercial Lighting Pendant is the ideal solution for warehouse, gymnasium, or other mid to high-ceiling applications where high output LED lighting is desired.


FEATURES


GRADI

Construction: Die-cast aluminum housing and heat sink Shade: Handblown glass shade Canopy: Canopy mounts to standard J-boxes Cord: 6 ft. power cord is standard CRI: 90+ Wattage: 21 watts Lumens: 2,125 delivered lumens Driver: 0-10V 5-wire 1% dimming Input Voltage: 120/277V, 50/60Hz Emergency Lighting: Optional remote 10watt emergency LED driver for lighting up to 90 minutes in event of power failure Listings: cUL listed for damp locations Warranty: 5 years carefree for parts & components (labor not included)




180°





WITH



150°

CP DISTRIBUTION

ORDERING INFORMATION Example: (15235-SL-WH-30K)

	I		I		I			
Model	Housing Cord Canopy Color		Glass Shade Color		Color Temperature		Options	
15235	SL	Silver	WН	White	ЗОК	3000K	EM7	Remote 10W Emergency
	WH	White	OR	Orange	35K	3500K		Back-Up Battery
			LA	Lavender	40K	4000K	ACX	Additional
			OB	Ocean Blue				Pendant Length
			0D	Occurr Dive				(Consult Factory)