

Project Name:

Quantity:

Shop Now

FIXTURE SPECIFICATIONS

Our RGBW color-changing cove LED light revolutionizes ambiance control with precision and versatility. Seamlessly transition between colors from anywhere on the color wheel or static white color temperature using remote, wall or Bluetooth app controls. The anodized, low-profile aluminum housing comes in a black, silver or custom finish and holds a frosted lens that uniformly distributes light with a 160° beam spread. The indoor IP54-rated model delivers 500 lumens per foot, while the IP65-rated model offers 250 lumens per square foot in outdoor and wet environments. This LED light is Title 24-compliant. Ideal for restaurants, bars, lounges, nightclubs, gymnasiums and other commercial applications.

FFATURES

Construction: Anodized Aluminum

Mounting: Installs on surface/corners

Finish: Silver, Black, White, and custom finishes are available.

Lens: Frosted Voltage: 24V LED fixture, 120-277V Driver

required for every 24' run.

Driver: 4N1 SERIES compatible with 0-10V, TRIAC (Forward-

phase), ELV

(Reverse-phase)

RGBW Control Options: Bluetooth App for iOS and Android, Remote Control with WiFi option, and Wall control with WiFi option.

Dimming: Dimmable via iOS/Android Apps or Controls

Beam Spread: 160°


Indoor: IP54 | 500 L/Ft | 5.5W/Ft Outdoor: IP65 | 250 L/Ft | 3.0W/Ft

Operating Temperature: -40°F (-40°C) ~ +140°F (+60°C)

CRI: 95+ Life: 50,000

Warranty: 5 years carefree for parts & components. (labor not included) Listings: UL listed, Title 24/JA8, Indoor (IP54) or outdoor (IP65) Buy American Act Compliant.





















ORDERING INFORMATION Example: (15255-2-30-BK-WL)

Model	Length	Color Temp	Finish	Options
15255-RGBW	2 2' 3 3' 4 4' 6 6' 8 8' XX 1 Custom	27 2700K 30 3000K 35 3500K 40 4000K 50 5000K	SL Silver Standard BK Black WH White RAL# Specify RAL # (Pg. 2)	WL ² Wet Location IP65

2 Wet Location for LED component only



AVAILABLE FINISHES

Standard

Sil	lver	Anodized Aluminum Finish
-----	------	-----------------------------

Set up fee and longer lead time will be applied on non-standard finishes.




Metropolitan RAL #9005 Black RAL #9003 White Asher Grey RAL #7004 RAL #7039 Mason Slate RAL #7031 Tech Grey RAL #7016 **Chocolate Spice** RAL #8017 **Urban Native** RAL #8025 Carmin RAL #8028 Reseda Green RAL #6011

Vibrant		
	Violet Dreams	RAL #4006
	Purple Red	RAL #3004
	Carmine Red	RAL #3002
	Rose	RAL #3017
	Pure Orange	RAL #2004
	Traffic Yellow	RAL #1023
	Daisy	RAL #1018
	Antique Spring	RAL #6019
	Island Skye	RAL #6027
	Sky Blue	RAL #5015




FIXTURE COMPONENTS


Aluminium channel




Frosted Lens



End Cap



Metal Mounting Clips








EXTERNAL DIMMING DRIVER SPECIFICATIONS


4N1 SERIES

Compatible with most TRIAC, ELV, MLV & 0-10V Dimmers


4N1-30W-24V




4N1-60W-24V




4N1-96W-24V




4N1-150W-24V



4N1-200W-24V



4N1-300W-24V









WIRING DIAGRAM

