SPECIFICATION SHEET

Quantity:

Type:

Shop Now



FIXTURE SPECIFICATIONS 6.75" (D) This fiberglass LED well light features an 0 open face cover to maximize light with a tempered glass lens and grill to protect Ó from environmental, walkway and oceanfront hazards. Suitable for soil or 0 C concrete. The in-ground light functions in almost any location. Also available with RGBW color-tuning technology. DETAILS Dia 6.75" x W 6.75" x H 8.10" Construction: Corrosion-resistant fiberglass 8.1" (H) Installation: Rated for in-ground soil and concrete applications 5.6" Lens: Clear, heat-resistant, tempered glass Finish: Bronze RGBW Controller: Bluetooth via Smart Life -Smart Living mobile app (Available for iOS and Android devices) CRI: 80+ Life: 35,000 Hours Listing: ETL approved for wet location, IP65

Project Name:



SPEC GRADE

ORDERING INFORMATION: Example: (9041-RGBW)

Model		Lamp Type		Color Temp	
9041	RGBW	RGBW 12W 1300 lms 120° Beam Spread 120V	(Bla	nk) RGB + W (27–64K)	
	W-25 W-40	White 18W 1200 lms 25° Beam Spread 120-277V White 18W 1200 lms 40° Beam Spread 120-277V	27 30 40 50	К 3000К К 4000К	